



Micro-Leak Detection System

For large packages

Leak detection for large packages or boxes, based on CO₂-technology. Leak Master® Pro features non-destructive detection of the smallest leaks without the need for costly Helium.

Benefits

- Minimal response time
- Quick product change
- For flexible and rigid packs
- No calibration required
- Operator friendly – data and process parameter entry by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- Easy-to-use intuitive system – no special skills required
- Convenient data administration and evaluation for customer oriented quality documentation
- Two chamber sizes (HxWxD) 140 x 680 x 500
230 x 680 x 500
- Easy installation and start-up
- Easy to clean splash-proof stainless steel cabinet /
- Potential free alarm contact for connection of external audible/visual device

Options

- Barcode Reader with IP-protection for simple and quick user/product selection
- Wireless data transmission via W-LAN (WIFI)

Two chamber sizes – 100%-analysis especially for large packages or boxes, e.g. E2.

Model	Chamber-size approx. in [mm] (H x W x D)	Cabinet /housing size approx. in [mm] (H x W x D)	Weight approx. [kg]	Pump capacity [kWh]	Pump suction capacity [m ³ /h]	Voltage
LM 12.1	230 x 680 x 500	1 025 x 760 x 855	225	2.20	100	400 V AC
LM 12.2	140 x 680 x 500	1 025 x 760 x 855	225	1.50	63	400 V AC

Caution! This equipment is not suitable for the checking of packaging featuring O₂ content greater than 20.9% (fresh meat, for example).



Water bubblers are becoming more and more popular

Better safe than sorry!

We have good news for the cylinder fillers:
Fast and reliable leak testing of CO2 cylinders for Sparkling Water Maker.

Contact us, we will be happy to advise you.



HTK Hamburg GmbH
Frahmredder 49
22393 Hamburg

Phone: +49 (0)40 - 600 38 38 - 0
Fax: +49 (0)40 - 600 38 38 - 99
info@htk-hamburg.com

© Copyright 2019 - All contents of this document, in particular Texts, photographs and graphics are protected by copyright. All rights, including reproduction, publication, processing and translation are reserved, HTK Hamburg GmbH. Please contact HTK Hamburg GmbH if you would like to use the contents of this document.

Technical Data	
Type	Leak Master® Pro
Measuring system	Infrared measuring cell for CO2
Measuring range	0 ppm - 5.000 ppm
Resolution	1 ppm
Warm-up time	Approx. 10 min.
Calibration	Not required
Response time	Approx. 1 sek.
Leak testing cycle	Depends on leak size, CO2-percentage in package, size of chamber
Vacuum	Max. 50 mbar abs.
Alarms	Potential free contact max. 250 V AC or 24 V DC/2 A
Interfaces	Ethernet (W-LAN optional)
Housing	Stainless steel, IP 54 splash-proof
Approvals	Company certified according to: ISO 9001:2015 CE marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU - Machinery safety 2006/42/EC For food-grade gases according to: - Regulation (EC) No 1935/2004

For non-destructive testing of smaller packages



Leak Master® Pro 2

Micro-leak detection system for packages based on CO2.

Leak Master® Pro 2 features non-destructive detection of the smallest leaks without the need for costly Helium.