



## Micro-Leak Detection System

### Especially durable and low in maintenance

Micro-leak detection system for packages based on CO<sub>2</sub>. Leak Master® Pro 2 features non-destructive detection of the smallest leaks without the need for costly Helium. Evacuated chamber with the help of a compressed air operated Venturi nozzle (optionally also with electric vacuum pump). Status indication by LED lighting of chamber.

#### Benefits

- visual indication of status via LED lighting
- short testing period by minimal response time
- quick product change
- for flexible and rigid packs
- especially durable and low in maintenance
- no calibration required
- standardised test processes - user independent
- operator friendly – data and process parameter entry by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- easy-to-use intuitive system – no special skills required
- convenient data administration and evaluation for customer oriented quality documentation
- various chamber sizes (see back side)
- easy installation and start-up
- easy to clean splash-proof stainless steel and acrylic glass cabinet / housing
- remote transmission of results via Ethernet

#### Options

- Barcode Reader with IP-protection for simple and quick user/product selection
- with electrical vacuum pump
- software Gascontrol Center for recording of results

#### Status



Measuring



Leak



OK

Rev.I\_022021\_Leak-Master Pro 2\_engl • Subject to change



We control GASES - since 1978



# Leak Master® Pro 2



Water bubblers are becoming more and more popular

**Better safe than sorry!**

We have good news for the cylinder fillers:  
Fast and reliable leak testing of CO2 cylinders for Sparkling Water Maker.

Contact us, we will be happy to advise you.



Technical Data	
Type	Leak Master® Pro 2
Measuring System	infrared measuring cell for CO2
Measuring range	0 ppm - 5.000 ppm
Resolution	1 ppm
Leak size measurements	> 10 µm (depending on the product and the test conditions)
Warm-up time	approx. 10 min.
Calibration	not required
Response time of the ensor	approx. 1 sec.
Leak testing cycle	depends on leak size, CO2-percentage in package, size of chamber
Vacuum	max. 200 mbar abs. (approx. -800 mbar to ambient pressure), adjustable
Vacuum generation	compressed air powered venturi injector
Compressed air pressure	min. 6 bar, max. 8 bar
Status	LED lighting
Interfaces	Ethernet (W-LAN optional)
Cabinet / Housing	stainless steel, acrylic glass IP 54 with closed chamber
Approvals	Company certified according to: ISO 9001:2015  CE-marked according to: EMV 2014/30/EU Low Voltage Directive 2014/35/EU  for food-grade gases according to: Regulation (EG) No 1935/2004



HTK Hamburg GmbH  
Frahmredder 49  
22393 Hamburg

Phone: +49 (0)40 - 600 38 38 - 0  
Fax: +49 (0)40 - 600 38 38 - 99  
info@htk-hamburg.com

© Copyright 2019 - All contents of this document, in particular Texts, photographs and graphics are protected by copyright. All rights, including reproduction, publication, processing and translation are reserved, HTK Hamburg GmbH. Please contact HTK Hamburg GmbH if you would like to use the contents of this document.

## Our Chamber sizes - for sample analysing



Model	Chamber-size approx. [mm] (inch) (H x B x T)	Housing-size approx. [mm] (inch) (H x B x T)	Weight approx. [kg]	Voltage
LM 2.1	42 x 310 x 200 (1.7 x 12.2 x 7.9)	316 x 364 x 405 (12.4 x 14.3 x 15.9)	20,0	100 - 230 V 50 - 60 Hz 50 W
LM 2.2	174 x 310 x 200 (6.9 x 12.2 x 7.9)	450 x 364 x 405 (17.7 x 14.3 x 15.9)	23,5	100 - 230 V 50 - 60 Hz 50 W
LM2.3	100 x 460 x 305 (3.9 x 18.1 x 12.0)	462 x 556 x 557 (18.2 x 21.9 x 21.9)	35,0	100 - 230 V 50 - 60 Hz 50 W

Caution! This equipment is not suitable for the checking of packaging featuring O2 content greater than 20.9%(fresh meat, for example).

Rev.I\_022021\_Leak-Master Pro 2\_engl • Subject to change



We control GASES - since 1978

